



SuperCash S

FISCAL CASH REGISTER WITH INTEGRATED GPRS TERMINAL

Main functions

- Fiscal cash register
- GPRS communication
- Support of remote management of cash registers
- Operating in fiscal printer mode

Advantages

- Integrated GPRS terminal guaranty low price, easy to handle, and higher reliability
- Quick and quiet thermal printing
- 2 alphanumeric LCD displays
- 10 buttons for quick sale of the most frequently sold items/services
- Possibility to monitor the products stock
- Easy load mechanism for paper roll
- Automatic rolling of paper tape journal
- Electronic journal option (SD card) instead of paper journal
- Selling using a barcode scanner
- Data processing on computer and PLU input into cash register
- Entry of Items via the keyboard in the same way as on a mobile phone
- The commands can be entered via the menu or directly by entering the command numeric code
- Resuming of an operation interrupted by a power supply failure and its proper finalizing
- Operation on locations w/out mains power supply (up to 8 h in operating mode) supported by rechargeable internal battery; Power Save function
- Easy to use



SuperCash S is fiscal cash register with integrated GPRS terminal enabling wireless connection to Tax Administration or customer remote server over mobile network. Beside basic FCR functions, this device supports centralized management of cash register in customer sales network and solves the problem of everyday data updating on articles stored in the remote cash register. Data are transferred through GSM network and Internet enabling the user to remote monitors all his cash registers regardless of their number or location. The SuperCash S can be delivered without GPRS terminal if it is not prescribed by the law.

Fiscal cash register function

SuperCash S allows to Tax Administration to do supervision of tax calculation in retail sale. There are two models – with control paper tape (model PJ) and with electronic journal (model EJ). The device has two RS-232 serial ports used for connection of barcode reader and for communication with PC. Computer data processing software and ECR PLU input software is delivered together with cash register. The cash registers supports 2 working modes. First, stand alone mode, uses keyboard and/or barcode reader for sale and second is fiscal printer mode where SuperCash is connected with PC sale application. Built-in Li-Ion battery makes possible operation on sales points w/out mains power system.

GPRS communication

GPRS terminal with built-in GSM/GPRS module ensures wireless communication of SuperCash S with remote servers. This terminal has its own IP address (fixed or dynamic) and performs two-ways data transfer by GPRS. It is programmable and manageable and equipped with real time clock and internal memory. Data storage into internal memory is performed automatically as well as reading and uploading of report to the server. GPRS terminal can be scheduled for accomplishing demanded activities for example, price changes, updating the items base, or reading daily reports on items sold. In the case of disconnection from the GSM network, the device makes the connection automatically when network access is possible.

SUPERCASH S



Technical specifications

FCR characteristics	Model PJ	Model EJ
Items (PLU)	9500	9500
Departments	100	100
Operators / cashiers	10	10
Payment options (cash, check and credit card)	3	3
Items per bill	400	400
Cash balance recording in the ECR memory after putting in and taking out money from the ECR	Yes	Yes
Items cancellation	Yes	Yes
Products stock control	Yes	Yes
Report types	Daily Z report, daily X report, periodical reports from the fiscal memory, per items, per departments, per operators, per hours	
Fiscal memory	2000 daily reports, up to 9 VAT rates, warning when less of 50 reports are left	
Printer type	thermal	thermal
Independent paper rolls	2	1 or 2
Printing of fiscal slips and reports	Yes	Yes
Printing speed	up to 14 lines/sec (65 mm/sec)	
Characters per line	18	38 (18 if 2 paper rolls are used)
Thermal paper tape	Ø up to 50 mm, 2 x 28 mm width	Ø up to 50 mm, 1 x 56 mm or 2 x 28 mm width
Printer lifetime	50 km of paper roll	
Alphanumeric displays with backlight	2 x LCD	
Display characters	16 x 1 line for customer, 16 x 2 lines for operator	
Keyboard	35 keys including 10 fast keys	
Real time clock	Yes	
GPRS terminal	GSM/GPRS module, Quad band GSM 850/900/1800/1900 MHz	
Power supply	built-in battery Li-Ion, 7.4 V, 1200 mAh external adapter AC 100-240 V, 50 Hz, DC 9 V, 1 A Power consumption 5 VA max in battery charge mode	
Interfaces	2 x RS-232 (for PC and bar-code reader) 1 x port for cash drawer Connector for external GSM antenna (optional)	
Dimensions	W x D x H: 143 x 310 x 91 mm	
Weight	1030 gr	

QMS
ISO 9001:2015

ISMS
ISO/IEC 27001:2014

CE certified

CONTACT US

www.geneko.rs

Geneko Sales Team
e-mail: fcrsales@geneko.rs

Geneko Support Team
e-mail: fcrsupport@geneko.rs

Bul. Despota Stefana 59a
11000 Belgrade • Serbia
Tel: +381 11 3340-591, 3340-178
Fax: +381 11 3224-437

